

PRIME-MINI

350kW DC EV Charger Compact & Powerful: The Smart CPO Choice



Scenarios



Parking



Commercial
Vehicle



Charging
Station

Specifications

Type		Split type
Input		480VAC, 3P+N+PE (Wye configuration) 50 / 60Hz
Output		200~950 VDC 350kW (Max.)
User Interface & Control		Touch LCD Panel
User Authentication		OCPP 1.6J / RFID / QR Code(optional) / Payment Card(optional)
Network Connection		Ethernet / Cellular(optional)
Ingress Protection		NEMA 3R
Mechanical	WxDxH	1455mm x 900mm x 1960mm (Cabinet) 800mm x 590mm x 1764mm (Terminal)
	Weight	<800kg(Cabinet) 、 <200kg(Terminal)
Protection		Overvoltage / Undervoltage / Overcurrent / Overtemperature / Surge Protection / Short Circuit / Leakage Current / Water Level Power Cut-off
Regulation Compliance		UL 2202 、 UL2231-1 、 UL2231-2 、 CSA C22.2 NO.107.1-16 、 CSA C22.2 No.281.1-12 、 CSA C22.2 No.281.2-12
Charging Time		10-20min

01

Ultra-Fast Charging

Certified for quality, performance, and reliability to meet global standards.

02

Patented Interactive Charging Management System

Smart power allocation lowers costs and optimizes energy use.

03

15.6"-LCD Touchscreen Display

Large interactive screen with intuitive UI-clear, easy, and user-friendly.

04

Flexible Layout & Smart Management

Split design saves space and supports OCPP for seamless remote management.

05

Minimalist Design-A Perfect Fit for Modern Cities

Minimalist look with branding options, seamlessly blending into urban spaces.



eTreego Co., Ltd.

service@etreego.com | TEL: +886 3 6579006 FAX: +886 3 6579556

No. 110, Xingong 3rd Rd., Zhubei City, Hsinchu County 302, Taiwan (R.O.C.)

